



# RD2X4

## QUAD REMOTE DISPLAY



Cardinal Scale's USA-made RD2X4 quad remote display provides readouts for multi-platform truck scales visible up to 150 feet away. The RD2X4's high-intensity LED display offers bright-red 2.25-inch-high digits that are highly visible even in direct sunlight. Ten brightness level settings let you select the exact intensity for the best visibility in your environment. This display is designed for truck weighing systems where the steering axle, drive axle, trailer axle, and total weight are shown to the truck driver. The IP66-rated mild steel cabinet features a rain hood and is painted industrial tan for long-lasting outdoor use. The cabinet comes with a post mount designed for 4-inch pipe (approx. 4.5-in OD).

The RD2X4 quad remote display has the capability to interface to RS-232 or 20mA current loop. The display's Auto Learn mode adapts to the data output for your indicator and is compatible with Cardinal Scale's USA-made 225 Navigator or 825 Spectrum weight indicators with multi-scale option cards. This auto format feature automatically selects input protocol based on the indicator for plug-and-play operation. There are no moving parts inside the display for long life and reliability. The front panel opens vertically for easy internal access.

- 150-foot reading distance
- Displays steering, drive, and trailer axles plus total weight
- Metal enclosure with rain hood for protection from the elements
- Auto Learn mode adapts to weight indicator protocols
- RS-232 or 20mA current loop connectivity
- For multi-platform truck scale operations
- Designed for outdoor or indoor use
- High-intensity 2.25-inch LED digits
- 10 brightness level settings
- USA-made quality



# SCOREBOARD RD2X4

## QUAD REMOTE DISPLAY

<b>Model</b>	RD2X4	
<b>Display</b>	Four individual stacked LED displays with 10 brightness levels	
	<b>Readout Designations</b>	Steering, Drive, Trailer, and Total
	<b>Digit Size</b>	Six-digit, seven-segment, 2.25-in / 57-mm-high digits
	<b>Annunciator Size</b>	Three-digit, sixteen-segment, 0.8-in / 2-cm high characters
	<b>Display Capacity</b>	-999999 to 999999
<b>Baud Rate</b>		2,400 - 38,400
<b>Data Bits</b>		7 or 8
<b>Character Format</b>		All standard ASCII characters
<b>Interface</b>		RS-232 serial and 20mA current loop
<b>Overall Dimensions</b>		16.7 in W x 26.8 in H x 7.9 in D / 42 cm W x 68 cm H x 20 cm D
<b>Viewing</b>	<b>Range</b>	150 ft / 46 m
	<b>Angle</b>	Visible in direct sunlight with an angle of +/- 70 degrees
<b>Enclosure</b>		Mild steel painted industrial tan with rain hood
<b>Post Mount</b>		Designed for 4-in pipe (approx. 4.5-in OD)
<b>Protection Rating</b>		IP66
<b>Power</b>	94 - 264 VAC, 47/63 Hz Universal Input	
	<b>Fuse</b>	4A max (located on power supply)
	<b>Cord</b>	6.3 ft / 192 cm length (Cardinal Part No. 6980-1030)
<b>Operating Environment</b>		-10 to 120° F (-23 to +49° C)
<b>Weight</b>	<b>Net</b>	37 lb / 17 kg
	<b>Shipping</b>	42 lb / 19 kg
<b>Indicator Compatibility</b>		Cardinal Scale model 225 or 825 indicators with multi-scale input option cards



Cardinal Scale reserves the right to improve, enhance, or modify features and specifications without prior notice.

**SOLD BY:**

 **Cardinal**  
Cardinal Scale Manufacturing Co.  
203 E. Daugherty, Webb City, MO 64870 USA  
Ph: 417-673-4631 or 800-441-4237 • Fax: 417-673-5001  
[www.CardinalScale.com](http://www.CardinalScale.com)

**Mobile:** [m.cardinalscale.com](http://m.cardinalscale.com)